



**NOTES:**

**ELECTRICAL:**

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5 AMP
3. CONTACT RESISTANCE: 100MILLIOHMS MAX
4. INSULATION RESISTANCE: 100 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN

**ENVIRONMENTAL:**

1. STORAGE: -40°TO+85°
2. OPERATION: 0°TO70°

**MECHANICAL:**

1. HOUSING MATERIAL: PC
2. INSERT MATERIAL: FAME RETARDANCY ABS
3. PCB MATERIAL: FR-4 T=1.6mm
4. CONTACT MATERIAL: PHOSPHOR BRONZE  
STAMP PIN T=0.30mm
5. RJ45 JACK ;LIFE: 750 TIMES MIN

				 <b>LANMASTER</b> LMASTER LIMITED Unit 1011, Wu Sang House, 655 Nathan Road, Kowloon, HK			
Number		Signature		Date		Material	Item No.
Drawn		2015.12.28		Tolerance		Angles Projection	Part Name
Checked		2015.12.28		0.00-20.00 ±0.10 20.00-50.00 ±0.15 50.00-100.00 ±0.20 100.00- Angle ±0.25 ±30°		Size	Scale
Approved		2015.12.28				A4	X:1
				Sheet		1 OF 1	Version: A/0
						Unit	
						mm	
						S/N	
						4 ports adapter	
						TWT-Y-1P4H	