

715 UNIVERSAL HOLLOW CORE



DRIVE



EXECUTION

- Tungsten-carbide coated

FOR USE IN



APPLICATION

- Only for rotary use
- Bayonet lock

PACKAGING



[144]

Comments

- 3 = Conduits
- 2 = Holes for pipes
- 1 = Sockets

D Ø mm			EAN 4016707...	12345
33,0	3	1	250026	715 000 033
53,0	2	1	250033	715 000 053
67,0	1	1	250040	715 000 067
73,0	1, 2	1	250057	715 000 073
83,0	2	1	250064	715 000 083

LOCATING PLATE FOR UNIVERSAL HOLLOW CORE



	EAN 4016707...	12345
1	250071	715 000 090

CENTRE DRILL BIT FOR UNIVERSAL HOLLOW CORE



D Ø mm	D Ø "	L1 mm		EAN 4016707...	12345
9,0	11/32	140	1	250095	715 090 140

UNIVERSAL HOLLOW CORE

- The cutting edges of all universal hollow cores are tungsten carbide coated. These carbide cutters which are attached with a high-temperature process ensure economic drilling in materials such as masonry, tiles, brick, breeze block and plasterboard.
- The fast replacement of hollow cores due to the simple bayonet lock and the light-weight design make things easy for the user.
- Can be used for sockets, holes for pipes, junction lines, conduits etc.

Safety Notes:

- Maximum speed in manual drilling machines 1,500 rpm
- Goggles must be worn