

1		2		3		4		5		6		7		8																																																																							
未注公差/General tolerances(mm)														符号/SIGN		描述/DESCRIPTION		修订者/DRAWN		日期/DATE																																																																	
<table><tr><td>>0</td><td>>3</td><td>>6</td><td>>10</td><td>>18</td><td>>30</td><td>>50</td><td>>80</td><td>>120</td><td>>180</td><td>>250</td><td>>315</td><td>>400</td><td>>500</td><td>0.1/10</td></tr><tr><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td>~</td><td></td></tr><tr><td>3</td><td>6</td><td>10</td><td>18</td><td>30</td><td>50</td><td>80</td><td>120</td><td>180</td><td>250</td><td>315</td><td>400</td><td>500</td><td></td><td></td></tr><tr><td>±0.15</td><td>±0.20</td><td>±0.25</td><td>±0.30</td><td>±0.35</td><td>±0.40</td><td>±0.60</td><td>±0.80</td><td>±0.95</td><td>±1.00</td><td>±1.20</td><td>±1.60</td><td>±2.20</td><td>±2.50</td><td>±2t</td></tr></table>														>0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10	~	~	~	~	~	~	~	~	~	~	~	~	~	~		3	6	10	18	30	50	80	120	180	250	315	400	500			±0.15	±0.20	±0.25	±0.30	±0.35	±0.40	±0.60	±0.80	±0.95	±1.00	±1.20	±1.60	±2.20	±2.50	±2t												
>0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10																																																																							
~	~	~	~	~	~	~	~	~	~	~	~	~	~																																																																								
3	6	10	18	30	50	80	120	180	250	315	400	500																																																																									
±0.15	±0.20	±0.25	±0.30	±0.35	±0.40	±0.60	±0.80	±0.95	±1.00	±1.20	±1.60	±2.20	±2.50	±2t																																																																							
Factory: Xiamen Fucon IMP.&EXP. CO.,LTD Part No.: PCT-2-3 PCT-2 - series of push wire connector (terminal) 3 - number of Pins (3 pins)																																																																																					
技术参数 Technical parameter:																																																																																					
<table><tr><td>● 产品标准/Rated Voltage</td><td colspan="3">IEC60947</td></tr><tr><td>● 获得安规及标志 Access to Safety Mark</td><td colspan="3"></td></tr><tr><td>● 证书号码/Certificate No</td><td colspan="3">R50543119</td></tr><tr><td>● 额定电压/Rated Voltage</td><td colspan="3">250V</td></tr><tr><td>● 额定电流/Rated Current</td><td colspan="3">32A</td></tr><tr><td>● 硬质导线/Solid wire</td><td colspan="3">0.2~4.0mm²</td></tr><tr><td>● 软质导线/Stranded wire</td><td colspan="3">0.2~2.5mm²</td></tr><tr><td>● 剥线长度/Wire strip length</td><td colspan="3">9~10mm</td></tr><tr><td>● 绝缘耐压/Withstanding Voltage</td><td colspan="3">2500V</td></tr><tr><td>● 温度范围/Operating temperature</td><td colspan="3">-40℃~105℃</td></tr><tr><td>● 位数/PIN</td><td colspan="3">1~8</td></tr><tr><td>● 关键尺寸/Critical dimension</td><td colspan="3">★</td></tr></table>														● 产品标准/Rated Voltage	IEC60947			● 获得安规及标志 Access to Safety Mark				● 证书号码/Certificate No	R50543119			● 额定电压/Rated Voltage	250V			● 额定电流/Rated Current	32A			● 硬质导线/Solid wire	0.2~4.0mm ²			● 软质导线/Stranded wire	0.2~2.5mm ²			● 剥线长度/Wire strip length	9~10mm			● 绝缘耐压/Withstanding Voltage	2500V			● 温度范围/Operating temperature	-40℃~105℃			● 位数/PIN	1~8			● 关键尺寸/Critical dimension	★																										
● 产品标准/Rated Voltage	IEC60947																																																																																				
● 获得安规及标志 Access to Safety Mark																																																																																					
● 证书号码/Certificate No	R50543119																																																																																				
● 额定电压/Rated Voltage	250V																																																																																				
● 额定电流/Rated Current	32A																																																																																				
● 硬质导线/Solid wire	0.2~4.0mm ²																																																																																				
● 软质导线/Stranded wire	0.2~2.5mm ²																																																																																				
● 剥线长度/Wire strip length	9~10mm																																																																																				
● 绝缘耐压/Withstanding Voltage	2500V																																																																																				
● 温度范围/Operating temperature	-40℃~105℃																																																																																				
● 位数/PIN	1~8																																																																																				
● 关键尺寸/Critical dimension	★																																																																																				
<table><tr><td>⑤</td><td>弹片</td><td>不锈钢</td><td>SUS301</td><td>6</td></tr><tr><td>④</td><td>铜件</td><td>紫铜</td><td>T2</td><td>3</td></tr><tr><td>③</td><td>手柄</td><td>阻燃尼龙</td><td>PA6-V0</td><td>6</td></tr><tr><td>②</td><td>上盖</td><td>阻燃尼龙</td><td>PA6-V0</td><td>1</td></tr><tr><td>①</td><td>主座</td><td>阻燃尼龙</td><td>PA6-V0</td><td>1</td></tr><tr><td>ITEM 序号</td><td>NAME OF PART 部件名称</td><td>Material 材料</td><td>NOTES 备注</td><td>QTY 用量</td></tr></table>														⑤	弹片	不锈钢	SUS301	6	④	铜件	紫铜	T2	3	③	手柄	阻燃尼龙	PA6-V0	6	②	上盖	阻燃尼龙	PA6-V0	1	①	主座	阻燃尼龙	PA6-V0	1	ITEM 序号	NAME OF PART 部件名称	Material 材料	NOTES 备注	QTY 用量																																										
⑤	弹片	不锈钢	SUS301	6																																																																																	
④	铜件	紫铜	T2	3																																																																																	
③	手柄	阻燃尼龙	PA6-V0	6																																																																																	
②	上盖	阻燃尼龙	PA6-V0	1																																																																																	
①	主座	阻燃尼龙	PA6-V0	1																																																																																	
ITEM 序号	NAME OF PART 部件名称	Material 材料	NOTES 备注	QTY 用量																																																																																	
<table><tr><td rowspan="4"></td><td colspan="2">CAT NO./认证型号</td><td colspan="2">PCT-2-xx</td><td colspan="2">SHEET: 1/1</td></tr><tr><td colspan="2">PATE NO./成品料号</td><td colspan="2">XX.XX.XXX.XXXX</td><td colspan="2">SCALE: 1:1</td></tr><tr><td colspan="2">CUST NO./客户料号</td><td colspan="2">/</td><td colspan="2">REV.: A01</td></tr><tr><td colspan="2">APPROVED/审核</td><td colspan="2">何晓雄 2022.04.12</td><td colspan="2">MODEL: PCT-2-3</td></tr><tr><td colspan="2">CHECKED/核准</td><td colspan="2">胡锦权 2022.04.12</td><td colspan="2">DRAWING NO./图号: PCT-2-001</td></tr><tr><td colspan="2">DRAWN/制图</td><td colspan="2">陈燕龙 2022.04.12</td><td colspan="2">TYPE/图纸类型: CUSTOMER_DRAWING</td></tr><tr><td colspan="2">SIZE: A4</td><td colspan="2"></td><td colspan="2"></td></tr></table>															CAT NO./认证型号		PCT-2-xx		SHEET: 1/1		PATE NO./成品料号		XX.XX.XXX.XXXX		SCALE: 1:1		CUST NO./客户料号		/		REV.: A01		APPROVED/审核		何晓雄 2022.04.12		MODEL: PCT-2-3		CHECKED/核准		胡锦权 2022.04.12		DRAWING NO./图号: PCT-2-001		DRAWN/制图		陈燕龙 2022.04.12		TYPE/图纸类型: CUSTOMER_DRAWING		SIZE: A4																																		
	CAT NO./认证型号		PCT-2-xx		SHEET: 1/1																																																																																
	PATE NO./成品料号		XX.XX.XXX.XXXX		SCALE: 1:1																																																																																
	CUST NO./客户料号		/		REV.: A01																																																																																
	APPROVED/审核		何晓雄 2022.04.12		MODEL: PCT-2-3																																																																																
CHECKED/核准		胡锦权 2022.04.12		DRAWING NO./图号: PCT-2-001																																																																																	
DRAWN/制图		陈燕龙 2022.04.12		TYPE/图纸类型: CUSTOMER_DRAWING																																																																																	
SIZE: A4																																																																																					