


# 340 HSS DIN 340 GROUND, SPLIT POINT, LONG



## DRIVE



## EXECUTION

- Profile-ground
- Right-hand cutting, type N
- High-performance high-speed steel
- Long, cylindrical
- 118° conical section
- Diametral tolerance h8


## FOR USE IN



## APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use

## PACKAGING



against  
surcharge

## Comments

- Other dimensions on request

D ø mm	L2 mm	L1 mm	d ø mm		EAN 4016707...	
2,00	56	85	2,0	10	070013	340 000 020
2,50	62	95	2,5	10	070020	340 000 025
2,90	66	100	2,9	10	070310	340 000 029
3,00	66	100	3,0	10	070037	340 000 030
3,20	69	106	3,2	10	070044	340 000 032
3,50	73	112	3,5	10	070051	340 000 035
3,80	78	119	3,8	10	070068	340 000 038
3,90	78	119	3,9	10	070327	340 000 039
4,00	78	119	4,0	10	070075	340 000 040
4,10	78	119	4,1	10	070082	340 000 041
4,20	78	119	4,2	10	070099	340 000 042
4,30	82	126	4,3	10	070105	340 000 043
4,50	82	126	4,5	10	070112	340 000 045
4,80	87	132	4,8	10	070129	340 000 048
4,90	87	132	4,9	10	070334	340 000 049
5,00	87	132	5,0	10	070136	340 000 050
5,10	87	132	5,1	10	070341	340 000 051
5,20	87	132	5,2	10	070143	340 000 052
5,50	91	139	5,5	10	070150	340 000 055
5,80	91	139	5,8	10	070174	340 000 058
6,00	91	139	6,0	10	070181	340 000 060
6,50	97	148	6,5	10	070198	340 000 065
7,00	102	156	7,0	10	070204	340 000 070
7,50	102	156	7,5	10	070211	340 000 075
8,00	109	165	8,0	10	070228	340 000 080
8,50	109	165	8,5	10	070235	340 000 085
9,00	115	175	9,0	10	070242	340 000 090
9,50	115	175	9,5	10	070259	340 000 095
10,00	121	184	10,0	10	070266	340 000 100
10,50	121	184	10,5	10	070273	340 000 105
11,00	128	195	11,0	10	070280	340 000 110
11,50	128	195	11,5	10	070297	340 000 115
12,00	134	205	12,0	10	070303	340 000 120