

1		2		3		4		5		6		7		8	
End-product drawing						REV.		DESCRIPTION				DESIGN		DATE	
						X1		NEW DRAWING				PDH		2019/10/10	

NOTES:
1.MATERIAL: PA66、BRASS、 SILICONE;
2.CERTIFICATION:ROHS/cUL/TUV/SAA/CE;
3.FIRE-PROOT:UL94-V2。
4.NO DEFECT IN APPEARANCE;
5.UNITS: mm;
6.CONDUCTION TEST:THE TWO ENDS OF THE 3 CORE JOINTS ARE RESPECTIVELY CONNECTED
7.A、 MAXIMUM CURRENT-CARRYING CAPACITY:400V/24A
B、 TEST VOLTAGE: 2500V
C、 SUITABLE FOR CABLES CROSS SECTIONS: 0.5-2.5mm²
D、 OPERATING TEMPERATURE RANGE: -40~+105℃
E、 PROTECTION CLASS: IP68

Silicone parts

ø15.8

øA

8.6

øA	Wire OD
ø11.5	ø9-12mm
ø8.5	ø5-9mm

35.5

24.3

25

24

17.5

24.4

Assembled 81 (REF)

Factory: Xiamen Fucon IMP.&EXP. CO.,LTD
Waterproof connector (coupling for lighting) with screw brass clamps for two cables

Part No.: EW-M20-3P
EW-M20 - series of waterproof connector (coupling)
3P - number of Pins (3 Pins)

Weight	MEAS	Each carton number	G.W.	UNLABELED TOLERANCE			UNITS	mm	DRAW	PDH 2019/10/10	PART NO.	EW-M20-3P	FUCON	
28g	42*30*34cm	600pcs	17.7Kg	X. ±0.35	X.XX ±0.20		X.° ±2°	SCALE	1:1	CHKD		DWG NO		
				X.X ±0.25	X.XXX ±0.10		X.X° ±1°	SHEET	1/1	APPD		TITLE		Waterproof connetor

1

2

3

4

5

6

7

8