

1		2		3		4		5		6		7		8							
未注公差/General tolerances(mm)														符号/SIGN		描述/DESCRIPTION		修订者/DRAWN		日期/DATE	
>0 ~ >3 ~ >6 ~ >10 ~ >18 ~ >30 ~ >50 ~ >80 ~ >120 ~ >180 ~ >250 ~ >315 ~ >400 ~ >500 0.1/10																					
3 6 10 18 30 50 80 120 180 250 315 400 500																					
±0.15 ±0.20 ±0.25 ±0.30 ±0.35 ±0.40 ±0.60 ±0.80 ±0.95 ±1.00 ±1.20 ±1.60 ±2.20 ±2.50 ±2																					
Factory: Xiamen Fucon IMP.&EXP. CO.,LTD																					
Part No.: PCT-2-2																					
PCT-2 - series of push wire connector (terminal)																					
2 - number of Pins (2 pins)																					
技术参数 Technical parameter:																					
● 产品标准/Rated Voltage IEC60947																					
● 获得安规及标志 Access to Safety Mark																					
● 证书号码/Certificate No R50543119																					
● 额定电压/Rated Voltage 250V																					
● 额定电流/Rated Current 32A																					
● 硬质导线/Solid wire 0.2~4.0mm²																					
● 软质导线/Stranded wire 0.2~2.5mm²																					
● 剥线长度/Wire strip length 9~10mm																					
● 绝缘耐压/Withstanding Voltage 2500V																					
● 温度范围/Operating temperature -40℃~105℃																					
● 位数/PIN 1~8																					
● 关键尺寸/Critical dimension ★																					
FUCON														CAT NO./认证型号 PCT-2-xx		SHEET: 1/1					
APPROVED/审核 何晓雄 2022.04.12														PATE NO./成品料号 XX.XX.XXX.XXXX		SCALE: 1:1					
CHECKED/核准 胡锦权 2022.04.12														CUST NO./客户料号 /		REV.: A01					
DRAWN/制图 陈燕龙 2022.04.12														MODEL: PCT-2-2							
SIZE: A4														DRAWING NO./图号 PCT-2-001							
TYPE/图纸类型: CUSTOMER_DRAWING																					