





Deep Groove Ball Bearing

d 100~110 mm







Principal dimensions				Basic load ratings		Limit speed ratings		
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil	
mm				kN		r/min		
100	215	47	3	173	141	2800	3600	
	215	47	3	173	141	2800	3600	
	215	47	3	173	141	2800	3600	
	215	47	3	173	141	2800	3600	
	215	47	3	173	141	3000	3600	
	215	47	3	173	141	3000	3600	
	215	47	3	173	141	2800	3600	
	250	58	4	214	184	2600	3400	
	250	58	4	214	184	2600	3400	
	105	130	13	1	19.9	21.9	4500	5300
160		26	2	73.0	62.8	4000	4800	
160		26	2	73.0	62.8	4000	4800	
160		26	2	73.0	62.8	4000	4800	
180		22	1.1	68.0	65.0	4200	5000	
180		22	1.1	61.5	59.5	4200	5000	
190		36	2.1	135	102	3200	3800	
190		36	2.1	133	105	3200	3800	
190		36	2.1	133	105	3200	3800	
190		36	2.1	135	102	3200	3800	
225		49	3	240	154	2800	3400	
110		140	16	1	24.8	28.0	4300	5000
		150	20	1.1	43.5	44.5	4000	4800
	150	20	1.1	43.5	44.5	4000	4800	
	170	19	1	57.2	57.0	3800	4500	
	170	28	2	82.0	70.6	3800	4500	
	170	28	2	82.0	70.6	3800	4500	
	170	28	2	82.0	70.6	3800	4500	
	200	38	2.1	145	114	2800	3400	
	200	38	2.1	145	114	2800	3400	
	200	38	2.1	132	106	3000	3600	
	240	50	3	195	167	2400	3000	
	240	50	3	195	167	2400	3000	
	240	50	3	195	167	2600	3200	
	240	50	3	151	169	2400	3000	

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6320A	113	202	2.5	7.10
6320M	113	202	2.5	8.94
6320M-DT	113	202	2.5	8.34
6320MA	113	202	2.5	9.28
6320M/CRA9	114	201	2.5	8.94
6320M/HQ1	114	201	2.5	8.00
6320/YA8	113	202	2.5	7.20
6420	116	234	3	13.1
6420M	116	234	3	16.2
61821M	110	125	1	0.468
6021	114	151	2	1.65
6021A	114	151	2	1.65
6021M	114	151	2	1.94
721	113.5	173.5	1	2.61
60121X1M	113.5	173.5	1	2.55
6221	116	179	2	3.85
6221/W124	117	178	2	3.66
6221/CRA9W124	117	178	2	3.66
6221M/CRA9	117	178	2	4.66
6321	118	212	2.5	8.05
61822	115	135	1	0.505
61922	116.5	143.5	1	0.888
61922M	116.5	143.5	1	1.01
16022	115	165	1	1.48
6022	119	161	2	1.92
6022M	119	161	2	2.35
6022M/YB5	119	161	2	2.35
6222	121	189	2	4.55
6222M	121	189	2	5.46
6222M/CRA9	122	188	2	5.46
6322	123	227	2.5	9.72
IS-6322M	123	227	2.5	11.7
6322-DT	123	227	2.5	9.72
6322/CM	123	227	2.5	9.23

Deep Groove Ball Bearing

d 110~130 mm







Principal dimensions				Basic load ratings		Limit speed ratings	
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil
mm				kN		r/min	
110	240	50	3	195	167	2600	3200
	240	50	3	195	167	2600	3200
	240	50	3	205	176	2400	3000
	240	50	3	205	176	2400	3000
	240	50	3	195	167	2600	3200
	280	65	4	247	226	2200	3000
280	65	4	247	226	2200	3000	
120	150	16	1	24.5	28.0	3800	4500
	165	22	1.1	53.0	54.0	3600	4300
	165	22	1.1	53.0	54.0	3600	4300
	180	19	1	60.5	64.0	3400	4000
	180	19	1	60.5	64.0	3400	4000
	180	28	2	85.5	80.0	3400	4000
	180	28	2	85.5	80.0	3400	4000
	180	28	2	85.5	80.0	3400	4000
	215	40	2.1	154	130	2800	3400
	215	40	2.1	155	132	2800	3400
	215	40	2.1	154	130	2800	3400
	215	40	2.1	155	132	2800	3400
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2200	2800
	260	55	3	217	196	2400	3000
	120.65	165.1	22.225	1.1	53.3	54.0	3600
121	165	22	1.1	53.3	54.0	3600	4300
127	228.6	34.925	2	148	133	2200	2800
130	165	18	1.1	37.0	38.0	3600	4300
	180	24	1.5	65.0	67.0	3400	4000

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6322/W124	124	226	2.5	9.72
IS-6322M	124	226	2.5	11.7
6322A	123	227	2.5	9.72
6322M	123	227	2.5	11.7
6322M/HQ1	124	226	2.5	10.5
6422	126	264	3	18.3
6422M	126	264	3	19.0
61824	125	145	1	0.566
61924	126.5	158.5	1	1.21
61924M	126.5	158.5	1	1.54
16024	125	175	1	1.64
16024M	125	175	1	1.82
6024	129	171	2	2.09
6024A	129	171	2	2.09
6024M	129	171	2	2.68
6224	131	204	2	5.28
6224/W124	132	203	2	5.30
6224M	131	204	2	6.68
6224M/CRA9	132	203	2	6.63
6324	133	247	2.5	12.5
6324-DT	133	247	2.5	12.5
6324A	133	247	2.5	12.5
6324M/C3	133	247	2.5	13.7
6324M-DT	133	247	2.5	14.8
6324F1/HQ1	133	247	2.5	13.4
6324/W124	134	245	2.5	12.5
619/121X4M	126.5	158.5	1	1.48
619/121M	126.5	158.5	1	1.48
66/127M	136	219.6	2	7.00
61826MA	136	159	1	0.969
61926M	138	172	1.5	1.92

Deep Groove Ball Bearing

d 130~140 mm







Principal dimensions				Basic load ratings		Limit speed ratings	
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil
mm				kN		r/min	
130	180	24	1.5	65.0	67.0	3400	4000
	190	19	0.7	56.0	60.0	3200	3800
	190	19	0.7	56.0	60.0	3200	3800
	200	22	1.1	79.5	81.5	3200	3800
	200	22	1.1	79.5	81.5	3200	3800
	200	33	2	109	98	3200	3800
	200	33	2	109	98	3200	3800
	200	33	2	109	98	3200	3800
	200	33	2	109	98	3200	3800
	230	40	3	153	134	2600	3200
	230	40	3	153	134	2600	3200
	230	40	3	153	134	2600	3200
	230	40	3	165	148	2600	3200
	230	40	3	165	148	2600	3200
	230	40	3	153	134	2600	3200
	280	58	4	251	241	2200	2600
	280	58	4	230	216	2200	2600
	280	58	4	240	226	2200	2800
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	251	241	2200	2600
	280	58	4	230	216	2200	2600
140	175	18	1.1	37.0	40.0	3400	4000
	175	18	1.1	37.0	40.0	3400	4000
	190	24	1.5	64.0	67.5	3200	3800
	210	22	1.1	80.5	86.5	3000	3600
	210	33	2	106	102	3000	3600
	210	33	2	106	102	3000	3600
	210	33	2	106	102	3000	3600
	210	33	2	106	102	3000	3600
	250	42	3	166	150	2400	3000
	250	42	3	166	150	2400	3000
	250	42	3	166	150	2400	3000
	250	42	3	128	150	2400	3000

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
61926	138	172	1.5	1.56
726	134	186	0.7	1.70
726H	134	186	0.7	1.91
16026M	136.5	193.5	1	2.32
16026	136.5	193.5	1	2.19
6026	139	191	2	3.29
FL-6026	139	191	2	3.29
6026M	139	191	2	3.96
6026MA	139	191	2	3.98
6226	143	217	2.5	6.33
6226M/CRA9	144	216	2.5	7.83
6226/W124	144	216	2.5	6.33
226HU1	143	217	2.5	7.51
226U1	143	217	2.5	6.16
6226MA	143	217	2.5	7.91
6326	146	264	3	15.3
6326-DT	146	264	3	15.1
6326/W124	147	263	3	15.3
6326A	146	264	3	14.9
6326F1/HQ1	146	264	3	16.7
FL-6326/HQ1	146	264	3	13.5
6326M	146	264	3	18.3
6326M-DT	146	264	3	17.6
61828M	146.5	168.5	1	1.00
61828MA	146.5	168.5	1	0.933
61928M	148	182	1.5	2.11
16028M	146.5	203.5	1	3.08
6028	146.5	201	2	3.47
6028/C9	149	201	2	3.47
6028/C9YB2	149	201	2	3.47
6028M	149	201	2	4.20
6228	153	237	2.5	7.41
6228/W124	154	236	2.5	7.41
6228M	153	237	2.5	9.28
6228MA	153	237	2.5	9.50

Deep Groove Ball Bearing

d 140~150 mm







Principal dimensions				Basic load ratings		Limit speed ratings	
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil
mm				kN		r/min	
140	250	42	3	166	150	2400	3000
	300	62	4	329	246	2000	2600
	300	62	4	329	246	2000	2600
	300	62	4	253	246	2000	2600
	300	62	4	253	246	2000	2600
	300	62	4	329	246	2000	2600
	300	62	4	253	246	2000	2600
	300	62	4	253	246	2000	2600
	300	62	4	253	246	2000	2600
	300	62	4	253	246	2000	2600
144	185	22	0.7	62.5	70.0	3600	4000
	185	22	0.7	48.0	70.0	3600	4000
149	201	33	0.7	105	102	3000	3600
	201	33	0.7	81.0	100	3000	3600
150	190	20	1.1	46.4	53.0	3000	3600
	210	28	2	84.5	90	2800	3400
	225	24	1.1	89.0	96.0	2600	3200
	225	24	1.1	89.0	96.0	2600	3200
	225	35	2.1	123	117	2600	3200
	225	35	2.1	123	117	2600	3200
	225	35	2.1	123	117	2600	3200
	225	35	2.1	123	117	2600	3200
	225	35	2.1	123	117	2600	3200
	225	35	2.1	123	117	2600	3200
	225	35	2.1	123	117	2600	3200
	230	35	2.1	123	117	2500	3000
	270	45	3	189	183	2000	2600
	270	45	3	189	183	2000	2600
	270	45	3	176	169	2000	2600
	270	45	3	176	169	2000	2600
	270	45	3	176	169	2000	2600
	320	65	4	360	280	1800	2200
	320	65	4	360	280	1800	2200
	320	65	4	360	280	1800	2200
	320	65	4	277	280	1800	2200
	320	65	4	360	280	1800	2200

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6228M/CRA9	154	236	2.5	9.28
6328	156	284	3	18.8
FL-6328/HQ1	156	284	3	16.7
6328-DT	156	284	3	18.8
6328L3-DT	156	284	3	20.7
6328/W124	157	283	3	18.8
6328M	156	284	3	21.5
6328M-DT	156	284	3	22.7
6328M/CRA9	157	283	3	21.5
928T3	148	181	0.7	1.07
66/144/S2	148	181	0.7	1.07
930T3	153	197	0.7	1.79
66/149/S2	153	197	0.7	1.79
61830M	156	184	1	1.50
61930M	159	201	2	3.04
16030	156.5	218.5	1	3.14
16030M	156.5	218.5	1	3.67
6030	161	214	2	4.07
FL-6030	161	214	2	4.07
6030/C9	161	214	2	4.07
6030M	161	214	2	4.98
6030M/P4	161	214	2	4.98
6030X1M	159	220	2.1	5.37
6230	163	257	2.5	9.96
6230/W124	164	256	2.5	9.96
6230M	163	257	2.5	11.4
6230M/W124	164	256	2.5	11.8
6230M/CRA9	164	256	2.5	11.4
6330	166	304	3	22.2
IS-6330	166	304	3	22.2
FL-6330/HQ1	166	304	3	18.3
6330-DT	166	304	3	22.2
IS-6330	166	304	3	22.2

Deep Groove Ball Bearing

d 150~170 mm







Principal dimensions				Basic load ratings		Limit speed ratings	
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil
mm				kN		r/min	
150	320	65	4	277	280	1800	2200
	320	65	4	277	280	1900	2400
160	200	20	1.1	49.5	59	2600	3200
	220	28	2	89	90.0	2600	3200
	229.5	33	3	108	111	2500	3100
	240	25	1.5	94.0	104	2400	3000
	240	25	1.5	94.0	104	2400	3000
	240	38	2.1	143	138	2400	3000
	240	38	2.1	143	138	2400	3000
	240	38	2.1	143	138	2400	3000
	240	38	2.1	127	127	2400	3000
	290	48	3	210	210	1900	2400
	290	48	3	200	201	1900	2400
	290	48	3	202	201	1900	2400
	290	48	3	200	201	1900	2400
	290	48	3	200	201	1900	2400
	290	48	3	202	202	1900	2400
	340	68	4	310	325	1800	2200
	340	68	4	310	325	1800	2200
	340	68	4	310	325	1800	2200
340	68	4	310	325	1800	2200	
340	68	4	238	325	1800	2200	
340	68	4	310	325	1800	2200	
165	250.5	35	2.5	147	143	2200	2600
170	215	22	1.1	65.0	61.0	2600	3200
	215	22	1.1	65.0	61.0	2600	3200
	215	22	1.1	65.0	61.0	2600	3200
	230	28	2	115	100	2400	3000
	230	28	2	115	100	2400	3000
	260	28	1.5	119	128	2200	2800
	260	28	1.5	119	129	2200	2800
	260	42	2.1	161	166	2200	2800
	260	42	2.1	161	166	2200	2800

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6330M	166	304	3	23.9
6330M/W124	167	303	3	26.0
61832M	168	192	1.1	1.32
61932M	169	211	2	3.28
62932X3M/YA6	168	211	3	4.67
16032	168	232	1.5	3.95
16032M	168	232	1.5	4.60
6032	171	229	2	5.04
6032/C9	171	229	2	5.04
6032M	171	229	2	6.04
6032M/W124	169	231	2	6.04
6232	173	277	2.5	12.4
6232-DT	173	277	2.5	12.3
6232M	173	277	2.5	14.2
6232M/P59Z2	174	276	2.5	14.4
6232M/CRA9	174	276	2.5	14.2
6232/W124	174	276	2.5	12.3
6332	177	323	3	25.7
6332-DT	177	323	3	26.5
6332M	176	324	3	30.7
6332M-DT	176	324	3	31.8
6332M/W124	177	323	3	30.5
6332/W124	176	324	3	25.7
733	177	238	2.5	6.44
61834M	176.5	208.5	1	2.03
61834M-Z/YA8	176.5	208.5	1	1.89
61834MA	176.5	208.5	1	1.98
61934M	179	221	2	3.42
61934MA	179	221	2	3.40
16034	178	252	1.5	5.01
16034M	178	252	1.5	5.83
6034M	181	249	2	7.96
6034MA	181	249	2	8.25

Deep Groove Ball Bearing

d 170~190 mm







Principal dimensions				Basic load ratings		Limit speed ratings		
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil	
mm				kN		r/min		
170	260	42	2.1	161	166	2200	2800	
	260	42	2.1	161	166	2200	2800	
	260	42	2.1	170	171	5300	4300	
	310	52	4	225	240	1900	2400	
	310	52	4	225	240	1900	2400	
	310	52	4	225	240	1900	2400	
	310	52	4	242	256	1900	2400	
	310	52	4	225	240	1900	2400	
	360	72	4	330	368	1700	2000	
	360	72	4	330	368	1700	2000	
	360	72	4	330	368	1700	2000	
	360	72	4	330	368	1700	2000	
	360	72	4	330	368	1700	2000	
	180	225	22	1.1	61.8	79.0	2400	3000
225		22	1.1	61.8	79.0	2400	3000	
250		33	2	118	128	2200	2800	
259.5		33	2	118	128	2200	2800	
259.5		52	2	118	128	2200	2800	
259.5		52	2	140	147	2200	2800	
280		31	2	135	145	2100	2700	
280		46	2.1	186	196	2200	2600	
280		46	2.1	186	196	2200	2600	
320		52	4	240	260	1800	2200	
320		52	4	240	260	1800	2600	
320		52	4	240	260	1800	2600	
380		75	4	340	400	1700	1900	
190		240	24	1.5	73.0	94.0	2200	2800
		260	33	2	127	138	2200	2800
	269.5	33	2	127	138	2200	2800	
	289.5	46	2.1	191	211	2000	2600	
	290	31	2	145	162	2000	2600	
	290	31	2	145	162	2000	2600	
	290	46	2.1	191	211	2000	2600	
	290	46	2.1	191	211	2000	2600	

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6034	181	249	2	6.86
6034Q1	181	249	2	8.06
4G134QT	181	249	2	7.94
6234	186	294	3	15.1
6234-DT	186	294	3	15.1
6234M	186	294	3	17.9
6234/YA5	186	294	3	15.2
6234M/CRA9	187	293	3	17.9
6334	186	344	3	31.5
6334-DT	186	344	3	31.5
6334M	186	344	3	38.4
6334M/W124	187	343	3	38.4
6334M/P59Z2	187	343	3	38.4
61836M	186	219	1	2.05
61836MA	186	219	1	2.17
61936M	189	241	2	5.07
61936X1M	189	241	2	6.05
63936X1M	189	250.5	2	8.64
63936X1F3-1/C3H	189	250.5	2	8.82
16036M	189	270	2	6.58
6036	191	269	2	8.75
6036M	191	269	2	10.4
6236	196	304	3	14.9
6236M	196	304	3	17.8
6236MA	196	304	3	18.7
6336M	198	363	3	49.5
61838M	198	232	1.5	2.63
61938M	199	251	2	5.85
61938X1M	199	260.5	2	5.78
6038X1M	201	279	2	10.8
16038	199	281	2	6.88
16038M	199	281	2	8.11
6038M	201	279	2	11.1
6038	201	279	2	9.58

Deep Groove Ball Bearing

d 190~230 mm







Principal dimensions				Basic load ratings		Limit speed ratings		
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil	
mm				kN		r/min		
190	340	55	4	265	305	1700	2000	
	340	55	4	265	305	1700	2000	
	340	55	4	265	305	1700	2000	
	340	55	4	265	305	1700	2000	
	400	78	5	370	440	1600	1900	
	400	78	5	360	425	1600	1900	
200	250	24	1.5	73.0	84.0	2200	2800	
	250	24	1.5	73.0	84.0	2200	2800	
	269.5	51	2.1	130	146	1900	2300	
	269.5	51	2.1	91.0	109	1900	2300	
	279.5	38	2.1	125	144	2000	2600	
	280	38	2.1	125	144	2000	2600	
	289.5	38	2.1	125	144	2000	2600	
	310	34	2	162	182	1900	2400	
	310	51	2.1	213	234	1900	2400	
	310	51	2.1	213	234	1900	2400	
	310	51	2.1	213	234	1900	2400	
	360	58	4	285	335	1700	2000	
	360	58	4	268	305	1700	2000	
	420	80	5	380	460	1600	1800	
	220	270	24	1.5	75.0	89.0	1900	2400
270		24	1.5	75.0	89.0	1900	2400	
300		38	2.1	148	176	1900	2400	
300		60	2.1	112	168	1900	2400	
309.5		38	2.1	148	176	1900	2400	
340		37	2.1	170	215	1800	2200	
340		56	3	242	284	1800	2200	
340		56	3	242	284	1800	2200	
400		65	4	297	365	1500	1800	
400		65	4	229	365	1500	1800	
460		88	5	403	520	1300	1600	
460		88	5	403	520	1300	1600	
230		329.5	40	2.1	190	227	1600	2000
		329.5	40	2.1	190	227	1600	2000

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6238	206	324	3	18.1
6238M	206	324	3	22.2
6238M-DT	206	324	3	21.1
6238M/CRA9	207	323	3	22.2
6338F3	210	382	4	48.4
6338M	210	382	4	50.0
61840MA	207	243	1.5	2.94
61840MA/P4	207	243	1.5	2.94
61040X1F3/C3H	208	260	2	7.91
61040X1M	208	260	2	8.10
61940X1MA-1	210	270	2	7.59
61940MA	210	270	2	7.63
61940X1MA	210	270	2	8.89
16040M	209	301	2	10.3
6040M	211	299	2	14.2
6040MA	210	300	2	14.3
6040	211	299	2	11.7
6240	216	344	3	22.3
6240M	216	344	3	26.4
6340	220	400	4	57.7
61844M	227	263	1.5	3.21
61844M/YA4	227	263	1.5	3.21
61944M	231	289	2	8.37
63944M	231	289	2	11.8
61944X1M	231	298.5	2	9.71
16044	233	327	2	11.7
6044	233	327	2.5	15.5
6044M	233	327	2.5	18.3
6244	236	384	3	31.2
6244M	236	384	3	36.3
6344	240	440	4	71.4
6344/C9	240	440	4	71.4
6646M	241	319	2.1	10.4

Deep Groove Ball Bearing

d 230~280 mm



Principal dimensions				Basic load ratings		Limit speed ratings		
d	D	B	r _{min}	C _r	C _{or}	Grease	Oil	
mm				kN		r/min		
230	309.5	40	2.1	145	173	1600	2000	
	329.5	40	2.1	190	227	1600	2000	
240	300	28	2	103	116	1800	2200	
	320	38	2.1	155	192	1800	2200	
	359.5	56	3	255	315	1700	2000	
	360	37	2.1	185	228	1700	2000	
	360	56	3	255	315	1700	2000	
	360	56	3	255	315	1700	2000	
	440	72	4	350	460	1300	1600	
	500	95	5	440	595	1100	1400	
	500	95	5	440	595	1100	1400	
	500	95	5	440	595	1100	1400	
	260	320	28	2	122	128	1700	2000
360		46	2.1	212	269	1600	1900	
360		46	2.1	212	269	1600	1900	
369.5		46	2.1	212	269	1600	1900	
369.5		68	2.1	227	288	1600	1900	
369.5		60	2.1	227	288	1600	1900	
369.5		60	2.1	227	288	1600	1900	
399.5		65	4	294	373	1500	1800	
370		46	2.1	212	269	1600	1900	
400		44	3	230	300	1500	1800	
400		65	4	294	373	1500	1800	
400		65	4	294	373	1500	1800	
480		80	5	430	592	1100	1400	
480		80	5	430	592	1100	1400	
480		80	5	430	592	1100	1400	
540		102	6	500	710	1000	1300	
540		102	6	500	710	1000	1300	
280		350	33	2	133	192	1600	1900
		380	46	2.1	215	282	1500	1800
	389.5	46	4	215	282	1500	1800	
	389.5	46	4	217	282	1500	1800	
	389.5	46	4	217	282	1500	1800	

Designations	Abutment and fillet dimensions			Weight
	D _{smin}	dh _{max}	r _{amax}	
	mm			kg
6646M-1/C3	241	319	2.1	9.02
6646M/W281	241	319	2.1	10.4
61848M	249	291	2	4.72
61948M	251	309	2	8.50
6048X1M	253	346.5	2.5	20.7
16048M	253	347	2	14.6
6048	253	347	2.5	17.6
6048M	253	347	2.5	20.7
6248	256	424	3	53.3
6348F1	260	480	4	95.0
6348F3	260	480	4	95.0
6348M	260	480	4	96.2
61852M	269	311	2	4.80
61952M	276	349	2	14.4
61952MA	271	349	2	14.4
61952X1M	276	349	2	16.3
62952X3M	271	358.5	2	22.9
62952X1M-1	271	358.5	2	20.3
62952X1F3-2/C3H	271	358.5	2	20.9
6052X1F3	276	384	3	28.5
752	271	359	2	16.5
16052M	272	388	2.5	22.3
6052M	276	384	3	28.4
6052M/YA3	276	384	3	26.6
6252/C3	280	460	4	68.8
6252F1	280	460	4	67.6
6252F3	280	460	4	67.6
6352F1	286	514	5	120
6352F3	286	514	5	120
61856M	289	341	2	7.30
61956M	291	369	2	16.4
61956X1M	291	379	2	18.3
61956X1M/W281	291	379	2	18.3