

PRO Bits



Robust quality bits for industrial use

WITTE PRO bits have proved their worth due to their consistently high quality – resulting from state-of-the-art production processes.

The complex hardening process guarantees permanent hardness of 59–61 HRC to meet tough requirements in industry and the trades.

PZ for POZIDRIV screws



BITFLEX
with the damping zone
between the drive and tip



DIN ISO1173

ITEM NO.	+	mm	1/4" drive
28045	PZ 1	25	6.3 mm
28046	PZ 2	25	6.3 mm
28047	PZ 3	25	6.3 mm

ITEM NO.	+	mm	1/4" drive
27043	PZ 0	25	C6.3
27045	PZ 1	25	C6.3
27046	PZ 2	25	C6.3
27047	PZ 3	25	C6.3
27052	PZ 2	32	C6.3
27053	PZ 3	32	C6.3
27048	PZ 4	32	C6.3



DIN ISO1173



Truncated tip
DIN ISO1173

ITEM NO.	+	mm	1/4" drive
27545	PZ 1	50	E6.3
27546	PZ 2	50	E6.3
27547	PZ 3	50	E6.3
27548	PZ 4	50	E6.3

ITEM NO.	+	mm	1/4" drive
27057	PZ 2	25	C6.3



DIN ISO1173



DIN ISO1173

ITEM NO.	+	mm	1/4" drive
27560	PZ 1	70	E6.3
27565	PZ 2	70	E6.3
27570	PZ 3	70	E6.3
27561	PZ 1	90	E6.3
27566	PZ 2	90	E6.3
27571	PZ 3	90	E6.3
27562	PZ 1	110	E6.3
27567	PZ 2	110	E6.3
27572	PZ 3	110	E6.3
27563	PZ 1	125	E6.3
27568	PZ 2	125	E6.3
27573	PZ 3	125	E6.3
27564	PZ 1	150	E6.3
27569	PZ 2	150	E6.3
27574	PZ 3	150	E6.3

ITEM NO.	+	mm	5/16" drive
27811	PZ 1	32	C8
27812	PZ 2	32	C8
27813	PZ 3	32	C8
27814	PZ 4	32	C8



DIN ISO1173



DIN ISO1173

ITEM NO.	+	mm	Drive 5.5 mm
30701	PZ 1	50	A5.5
30702	PZ 2	50	A5.5
30703	PZ 3	50	A5.5

ITEM NO.	+	mm	7.0 mm drive
30801	PZ 1	53	G7
30802	PZ 2	53	G7
30803	PZ 3	53	G7