



















1		2		3		4		5		6		7		8							
A	Raw Material		PA66、SILICONE、 COPPER ALLOY		3 PIN  Pole Female connector Pin Male connector								REV		DESCRIPTION		DESIGN		DATE		
	Certification		UL/CQC/RoHS/CE										A0		NEW DRAWING		Andy. Pi		2022/4/7		
	Flame-resistant rating		UL94 V-0																		
	Level of protection		IP68																		
	Voltage rating/Current rating		450 V / 20 A																		
B	Withstanding voltage		2500 V																		
	Cable gague		0.5~2.5mm²																		
	Operating temperature		-40~105 ℃																		
C	Part Number		Rubbers Diameter(d)		Outer Cable Diameter		Factory: Xiamen Fucon IMP.&EXP. CO.,LTD Waterproof coupling (female connector and male connector for lighting) with screw copper alloy clamps for two cables Part No.: EW-M19MF-03X01 EW-M19MF - series of waterproof coupling (female connector and male connector) 03 - number of Pins (3 Pins) X01 - no value														
			φ 10.2 mm		φ 7~10 mm																
			φ 8.1 mm		φ 5~8 mm																
			φ 6.5 mm		φ 3.5~7 mm																
D	Rubbers Diameter		 56(REF) 102(REF) 56(REF)      																		
E			 56(REF) 102(REF) 56(REF)      																		
F			 56(REF) 102(REF) 56(REF)      																		
20g		42x30x26 cm		1000 PCS		20.7 Kg		TOLERANCE UNSPECIFIED		UNIT		mm		DRAW		P/N		EW-M19MF-03X01		FUCON	
Weight		MEAS		Each carton number		G. W.		X. ±0.35 X.XX ±0.10 X.° ±3° X.X ±0.20 X.XXX ±0.05 X.X° ±2° X.XX° ±1°		SCALE		1:1		CHKD		D/N					
										SHEET		1/1		APPD		TITLE		EW-M19MF WATERPROOF CONNECTOR			
1		2		3		4		5		6		7		8							