


# 329 HSS COUNTERSINK 90° KEILBIT



## DRIVE



D ø mm	L1 mm	SW mm	d ø mm	M	Icons	EAN 4016707...	12345
6,30	31	6,35	6,3	3	1	150388	329 000 063
8,30	31	6,35	6,3	4	1	150395	329 000 083
10,40	34	6,35	6,3	5	1	150401	329 000 104
12,40	35	6,35	6,3	6	1	150418	329 000 124
16,50	40	6,35	6,3	8	1	150425	329 000 165
20,50	41	6,35	6,3	10	1	150432	329 000 205

## EXECUTION

- Cutting head according to DIN 335 C
- 1/4" bit drive DIN 3126 - C 6.3
- 3 cutting edges
- Radial and axial relief

## FOR USE IN




- Deburring and drilling of uniformly circular counter sink holes with a smooth surface
- Suitable for almost all materials
- The best results are obtained at low speeds and a high feedrate

## APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use
- In all drilling machines, cordless screw drivers and bit holders with 1/4" drill shank
- SDS-plus locating shank for Bits and KEILBIT [37]
- Quick bit holder for bits and KEILBIT [72]

## PACKAGING



[154]

## Comments

- Individual packaging with hanger