



STRONG. RESISTANT. INVINCIBLE.

ROW-CROP CULTIVATOR CHOPSTAR-TITAN

The CHOPSTAR-TITAN high-residue row-crop cultivator can be used with row distances of 45 to 80 cm / 18-32", e.g. in soybean, corn, or sunflowers. It was designed for professional hoeing in organic material such as mulch seeding or strip till. Its centerpiece is a large sweep with a pre-running vertical cutting disc. The TITAN also impresses with its robustness and aggressiveness, making it the expert choice for difficult operating conditions.

Depending on the conditions of use and the objective of the hoeing pass, a wide range of tools can be attached to the TITAN, such as camera steering system, parallelogram lift, following weeder tines, finger weeders, rotative weeders, protection elements, and a wide variety of tines, sweeps, knives, etc."



Rows	Row distance in cm	Frame	Transport width ~ m ~ ft.		Frame width ~ m ~ ft.		Tines	Body	from hp/kW	Weight kg lbs	
6	50	S	3,20	10,5	3,20	10,5	7	7	60/44	680	1 500
4	75	S	3,20	10,5	3,20	10,5	5	5	60/44	570	1 260
8	50	K	3,00	9,8	4,20	13,8	9	9	90/66	1 060	2 340
6	75	K	3,00	9,8	4,70	15,4	7	7	90/66	950	2 090
12	50	K	3,00	9,8	6,20	20,3	13	13	130/96	1 350	2 980
8	75	K	3,00	9,8	6,20	20,3	9	9	130/96	1 120	2 470

S = rigid | K = foldable | P = double folding frame

Einböck CHOPSTAR row-crop cultivators are individually configured using a flexible hoeing technology modular system. Therefore there is no fixed standard equipment - each machine is perfectly tailored to the user's requirements.

STANDARD EQUIPMENT

- ✓ Robust, durable & special profile-tube frame with high frame clearance (rigid, single-fold or with double folding frame)
- ✓ Various tractor attachments, e.g., via the ROW-GUARD sideshift frame, Cat. 2, Cat. 3, or with upper link steering
- ✓ TITAN hoeing element with centered TITAN hoeing sweep, adjustable in the angle for row distances up to 80 cm / 32" and/or up to 3-tine configuration
- ✓ Large-dimensioned parallelograms for maximum height adjustment and durability, including main frame quick fixation
- ✓ Height adjustable double Farmflex depth-control wheels, ball-bearing mounted
- ✓ Parallelogram down pressure adjustable
- ✓ Various hoeing tools such as vibro-tine, carbide metal duckfoot sweeps, angle knives, heaping sweeps, etc.

OPTIONS

- » VERSO equipment – the cutting disc/angle knife combination
- » Vertical cutting disc centered in front of the middle TITAN sweep for precutting through organic material
- » Trailed working tools such as finger weeders, following weeder tines, rotative weeder, hilling discs, etc.
- » Quick-change function for trailed working tools
- » Finger weeder with its own parallelogram, SMART-GRIP or SIMPLE-GRIP quick adjustment, and spring-loaded
- » Various crop protection elements, can be raised, height adjustable, with quick adjustments and parallelogram-guided (depending on version)
- » Hydraulic parallelogram lifting SECTION-CONTROL with up to 35 cm / 14" lifting height and simultaneous lifting of the hoeing element and trailed working tools, including neat hose routing
- » Camera sideshift frame ROW-GUARD
- » P-BOX seeding box, JUMBO-SEED front tank
- » JUMBO-STREAM liquid front tank
- » Warning signs with holder and LED lights
- » Many other special configurations and custom-made tools/parts



www.einboeck.at/en/titan