



SPECIFICATION

Number of furrows		3+1	4+	4+1	5+	5+1
	mm	140x140 				
	cm	33-38-44-48				
	mm	1000				
	Memory cylinder					

MAXGREEN

	protection	SHEAR BOLT 				
	hp	100 - 250		150 - 350		
	mm	800 - 820				
	kg	1170	1323	1540	1620	1740

STANDARD EQUIPMENT:

- Mouldboard: KV09, LM35, LM40
- Extension wings for LM35, LM40
- Hydraulic cylinder with automated unit for turning
- Fork hinge cat. 3
- Front furrow adjustment
- Runner foot on last pairs of mouldboards
- Support wheel AW 702 (Ø 765x265)
- Adjustment of traction line
- In protection by BOLT - adjustment of angle of aggressivity of mouldboard

PROTECTION BY BOLT:



OPTIONAL EQUIPMENT:

- Trashboards
- Mouldboard PS40
- Mouldboard KV28 - extra long
- Extension wing KV09
- Memory cylinder (just for 3+1)
- Bolt skimmer type S /Skimmer Spring type S
- Bolt skimmer type K /Skimmer Spring type K
- Rolling coulter Ø 480 /Rolling coulter Spring Ø 480 (PRO)
- Sword landsides
- Support wheel TR315 with tread (Ø 590x255)
- Back support wheel TR315 with tread (Ø 590x255) and shock absorber
- Combined transport wheel (PRO) with shock absorber