



FOCUSED. NARROW. SHALLOW.

GRAIN ROW-CROP CULTIVATOR CHOPSTAR-MINI

The CHOPSTAR-MINI (formerly CHOPSTAR 1-30 / EGS) has 1 tine per hoeing element and can be used in row-crops with a row spacing of up to 35 cm / 14", e.g. cereals, field beans, lupins, etc. Depending on the conditions and the aim of the hoeing pass, weeder tines mounted behind the element or different sweeps (such as ultra-flat) can be mounted on the front or rear hoeing machine.

The precision of the CHOPSTAR-MINI can be further optimized with the camera steering and the ROW-GUARD sideshift frame, the SECTION-CONTROL parallelogram lift and other additional options.



Rows	Row distance in cm	Frame	Transport width		Frame width		Tines	Body	from hp/kW	Weight	
			~ m	~ ft.	~ m	~ ft.				kg	lbs
12	25	S	3,20	10,5	3,20	10,5	13	13	40/30	700	1 540
16	25	K	3,00	9,8	4,20	13,8	17	17	70/51	1 200	2 650
24	25	K	3,00	9,8	6,20	20,3	25	25	80/59	1 560	3 440
32	25	K	3,30	10,8	8,20	26,9	33	33	90/66	2 120	4 670

S = rigid | K = foldable | P = double folding frame

Einböck CHOPSTAR row-crop cultivators are individually configured using a flexible hoeing technology modular system. Therefore there is no fixed standard equipment - each machine is perfectly tailored to the user's requirements.

STANDARD EQUIPMENT

- ✓ Robust, durable & special profile-tube frame with high frame clearance (rigid, single-fold or with double folding frame)
- ✓ Various tractor attachments, e.g., via the ROW-GUARD sideshift frame, Cat. 2, Cat. 3, or with upper link steering
- ✓ MINI hoeing element for row distances up to 35 cm / 14" and 1-tine configuration
- ✓ Large, readjustable parallelograms for maximum height adaption and durability, including main frame quick fixation
- ✓ Parallelogram down pressure adjustable
- ✓ Height adjustable Farmflex depth-control wheels with ball bearing, ø 300 mm / 100 mm
- ✓ Various hoeing tools such as vibro-tine, carbide metal duckfoot sweeps, angle knives, heaping sweeps, etc.

OPTIONS

- » Following weeder tines
- » Various crop protection elements, can be raised, height adjustable, with quick adjustments and parallelogram-guided (depending on version)
- » Hydraulic parallelogram lifting SECTION-CONTROL with up to 35 cm / 14" lifting height, including neat hose routing
- » Camera sideshift frame ROW-GUARD
- » P-BOX seeding box, JUMBO-SEED front tank
- » JUMBO-STREAM liquid front tank
- » Warning signs with holder and LED lights
- » Many other special configurations and custom-made tools/parts



For hoeing grain, peas, lupine, etc.