



### SPECIFICATION

(DOWNHIL 850, DOWNHIL)

| Number of furrows                                                                  |    | 2+         | 2+1 | 3+       | 3+1       |
|------------------------------------------------------------------------------------|----|------------|-----|----------|-----------|
|   | mm | 120x120x10 |     |          |           |
|   | mm | 850        |     |          |           |
|  | hp | 60 - 90    |     | 80 - 110 | 100 - 160 |

### DOWNHIL

|                                                                                     |            |                                                                                                  |     |  |      |
|-------------------------------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------------|-----|--|------|
|  | protection | SHEAR BOLT  |     |  |      |
|  | mouldboard | KV09, LM35, LM40                                                                                 |     |  |      |
|  | cm         | 28 - 32 - 37 - 43                                                                                |     |  |      |
|  | mm         | 800 - 820                                                                                        |     |  |      |
|  | kg         | 770                                                                                              | 983 |  | 1210 |

### STANDARD EQUIPMENT:

- Mouldboard: KV09, LM35, LM40, (possibility JR30, SR30 for SPRING version)
- Extension wings for JR30, SR30, LM35, LM40
- Hydraulic cylinder with automated unit for turning
- Support wheel (Ø 710x265)
- Fork hinge cat. 2
- Front furrow adjustment

### PROTECTION BY BOLT:



### OPTIONAL EQUIPMENT:

- Trashboards
- Mouldboard PS40
- Mouldboard KV28 - extra long
- Extension wing KV09
- Memory cylinder
- Bolt skimmer type S /Skimmer Spring type S
- Bolt skimmer type K /Skimmer Spring type K
- Rolling coulter Ø 480 /Rolling coulter Spring Ø 480
- Sword landsides
- Support wheel TR315 with tread (Ø 590x255)
- Back support wheel TR315 with tread (Ø 590x255) and shock absorber
- Combined transport wheel