

TRAILER T-617/5

TECHNICAL SPECIFICATIONS | EQUIPMENT



WARRANTY
24 months



WARRANTY
48 months
on galvanized parts

Year of model 2022

CynkoMet®
Czarna Białostocka

TECHNICAL SPECIFICATIONS	
Type / Variant / Version according to EU homologation	T-4 620 61
Administrative loading capacity	~ 12,040 kg*
Technical loading capacity	~ 15,500 kg* (16,500 kg with K80 tension member)
Gross vehicle weight rating according to PL regulations	17,540 kg
Gross vehicle weight rating according to Directive 2015/208 (only load on axles)	14,540 kg
Kerb weight (without wall extensions)	~5,500 kg* (with extensions - standard) ~ 5,000 kg* (without extensions)
Number of axles	2 (tandem)
Length	7,230 mm
Width	2,550 mm
Height without extensions	~2,365 mm
Height with extensions	~3,165 mm
Box type	Side-wall, pallet type
Length of cargo box interior	5,140 mm
Width of cargo box interior front/rear	2,430 mm
Height of box walls (without extensions)	1,600 mm (800+800)
Height of platform from base	~1,565 mm
Floor/wall sheet thickness	5 / 2 mm
Loading surface	12.5 m ²
Loading capacity - without extensions (with extensions)	10 m ³ (20 m ³)
Track of wheels	1,900 mm
Wheelbase	1,320 mm
Suspension	parabolic springs
Max. vertical drawbar eye load	3,000 kg (4,000 kg with K80 tension member)
Drawbar coupling height – min.	one drawbar distance piece (standard) - 690 mm distance piece + plate - 630 mm two drawbar distance pieces - 510 mm
Drawbar coupling height – max.	
Max. tolerable vertical load on axle	1. 7,270 kg 2. 7,270 kg
Tire size	385/65 R22.5
Design speed	40 km/h
Minimum demand for tractor power	73.5 kW / 100 HP
Tipping angle of the cargo box (backward / sideways)	45 / 50
Tipping system	three-way

* - unladen weight and loading capacity may differ depending on the trailer's equipment

STANDARD MACHINE EQUIPMENT

Wall height 800 mm with thickness 2 mm, hot-galvanized - split side walls

Wall extensions, height 800 mm with thickness 2 mm, hot-galvanized - split side wall extensions

Central bolt-locking of walls (bottom sideboards)

Exterior ladder and steps inside cargo box - hot-galvanized - with anti-skid steps facilitating access to cargo box

Maintenance support of cargo box, hot-galvanized

Hot-galvanized drawbar with exchangeable eye, rubber shock absorbers, homologated

Bolted hitch tension member dia. 50

Hot-galvanized frame of cargo box

Main stringers (with variable cross-section) of cargo box frame made of bent high-strength sheets 6mm thick. Profile cross-section at highest point 110x300 mm

Galvanized cargo box floor welded out of two sheets with a thickness of 5 mm, bolted and riveted

Hot-dip galvanized bottom frame (protection of the structure on the exterior and interior of profiles), stringers of the frame made of 250x150x8 closed sections

Parking handbrake with crank

Grain chute, hot-galvanized, with blockade in the rear wall

Hydraulic drawbar support with built-in hydraulic lock

Homologated, hot-galvanized bumper

Side wall links

Pallet width

Tipping installation protected against excessive box inclination by cut-off valve

Lighting installation connector cable with 7PIN 12V plug

12V lighting, homologated, rear bulb lamps, LED perimeter lighting

Hydraulic installations made of galvanized steel tubes and flexible hoses

Hydraulic connectors to tractor, type ISO 7241-1 DN 12.5

Homologated, double-circuit, pneumatic brake system with automatic braking force adjustment, with output for second trailer.

Rear hydraulic, electrical and brake output to the second trailer

New 385/65 R22.5 wheels

Axles from renowned ADR company, full beam with 100 mm square cross-section, 406 x 120 brake

Parabolic leaf spring suspension

Two wheel chocks placed in galvanized pockets

Telescopic actuator with articulated suspensions, five-level with 1980 mm pitch. Nominal force at fifth level with diameter 140 mm, at nominal pressure 20 MPa = 307.9kN (31.4T)

Wheel fenders

OPTIONAL MACHINE EQUIPMENT
Spare wheel winch with hot-galvanized wheel hanger
Hot-galvanized tarpaulin frame made of 40x40x3 closed profiles
Chute for precise tipping, hot-galvanized
Hot-galvanized work platform
Full LED lighting
Homologated, hydraulic double-circuit brake system with automatic braking force adjustment
Surcharge for "new" 550/60 R22.5 wheels
385/65 R22.5 "new" spare wheel
550/60 R22.5 "new" spare wheel
Roll-up tarpaulin
Hydraulic quick-coupler with pressure neutralizer in hose
Warning triangle (sign distinguishing slow-moving vehicle)
DUPLEX - painted set of walls
DUPLEX - painted set of extensions
Hitch tension member K80
Set of side (bicycle) guards
Automatic hitch for second trailer
Manual hitch for second trailer

The data and photographs given in the catalog are for illustrative purposes only. This document and the information it contains, including prices, do not constitute a commercial offer within the meaning of art. 66 of the Civil Code. This information may be subject to change as products are continuously improved. We reserve the right to change a product's characteristics at any time. Products' specifications may change without notice. Realization of an order begins when a person from our sales department confirms the data contained in the order form.



**HOT-
GALVANIZED CONSTRUCTION**

