



WIDE. CLEAR. FIRM.

FRONT ROW-CROP CULTIVATOR CHOPSTAR-FRONT

The CHOPSTAR-FRONT front row-crop cultivator can be used with row distances of 45 to 150 cm, e.g. in soybean, corn, pumpkin, or sunflower. Depending on the row distance, 3, 5, or up to 10 sweeps are installed. The pushed front row-crop cultivator can be equipped with additional working tools such as finger weeder, following weeder tines, crop protection elements, or hilling tools. A track indicator assists the driver for optimum visibility.



For hoeing corn, soybean, pumpkins, etc. at the front—designed for the narrowest tractor cultivation!



Rows	Row distance in cm	Frame	Transport width		Frame width		Tines	Body	from hp/kW	Weight	
			~ m	~ ft.	~ m	~ ft.				kg	lbs
2	150	S	3,00	9,8	3,20	10,5	20	3	40/30	440	970
3	150	K	3,00	9,8	4,70	15,4	30	4	60/44	900	1 980
3	45	S	1,60	5,2	1,55	5,1	10	4	30/22	335	740
4	45	S	2,00	6,6	2,00	6,6	13	5	30/22	400	880
6	45	S	3,00	9,8	2,90	9,5	19	7	40/30	530	1 170
8	45	K	3,00	9,8	3,80	12,5	25	9	60/44	830	1 830
12	45	K	3,00	9,8	5,60	18,4	37	13	70/51	1 160	2 560
2	70	S	1,60	5,2	1,60	5,2	11	3	20/15	340	750
4	70	S	3,00	9,8	3,00	9,8	21	5	40/30	430	950
4	70	K	3,00	9,8	3,00	9,8	21	5	50/37	570	1 260
6	70	S	4,40	14,4	4,40	14,4	31	7	60/44	560	1 230
6	70	K	3,00	9,8	4,40	14,4	31	7	60/44	860	1 900
7	70	K	3,00	9,8	5,10	16,7	36	8	70/51	940	2 070
8	70	K	3,20	10,5	5,80	19,0	41	9	80/59	1 020	2 250

S = rigid | K = foldable | P = double folding frame

Einböck CHOPSTAR row-crop cultivators are individually configured using a flexible hoeing technology modular system. Therefore there is no fixed standard equipment - each machine is perfectly tailored to the user's requirements.

STANDARD EQUIPMENT

- ✓ Robust, durable & special profile-tube frame with high frame clearance (rigid, single-fold or with double folding frame)
- ✓ FRONT hoeing element for row distances from 45 cm / 18 up to 150 cm / 60" and 3 or 5/10-tine configuration
- ✓ Large, readjustable parallelograms for maximum height adaption and durability, including main frame quick fixation
- ✓ Parallelogram down pressure adjustable
- ✓ Height adjustable Farmflex depth-control wheels with ball bearing, ø 300 mm / 100 mm
- ✓ Various hoeing tools such as vibro-tine, carbide metal duckfoot sweeps, angle knives, heaping sweeps, etc.

OPTIONS

- » Trailed working tools such as finger weeders, following weeder tines, rotative weeder, hilling discs, etc.
- » Various crop protection elements, can be raised, height adjustable, with quick adjustments and parallelogram-guided (depending on version)
- » Camera sideshift frame ROW-GUARD
- » P-BOX seeding box, JUMBO-SEED front tank
- » JUMBO-STREAM liquid front tank
- » Warning signs with holder and LED lights
- » Many other special configurations and custom-made tools/parts