




ARCOAGRO 180 ON-LAND

Number of furrows		5+	5+1/ 6+	7 (6+1)	8 (6+1+1)	9 (7+1+1)
	kg	2977	3220	3463	3733	4000
	hp	180 - 250	180 - 300	230 - 300	240 - 400	270 - 500
	protection	SHEAR BOLT 				
	mm	1000				
	cm	35-41-47				
	mm	800 - 820				
	mm	180x180x10 				

STANDARD EQUIPMENT:

- Mouldboard: KV09, LM35, LM40
- Trashboards
- Extension wings for LM35, LM40
- Fork hinge cat. 3
- Wheel FLOTATION 500/45-22,5
- Vacuum hydraulic accumulator
- Box + 2 spanners
- System On-land
- In protection by BOLT - adjustment of angle of aggressivity of mouldboard

SYSTEM ON-LAND (width 4m)



PROTECTION BY BOLT:



OPTIONAL EQUIPMENT:

- Mouldboard PS40
- Mouldboard KV28 - extra long
- Extension wing KV09
- Link ball and pin for tractor of cat.4
- Bolt skimmer type S
- Bolt skimmer type K
- Rolling coulter Ø 480
- Sword landsides
- Lightning

- **On-land** front supporting wheels
- **On-land** main frame support wheel (separately)