



REWARDING. PROVEN. DYNAMIC.

GRASSLAND WEEDER GRASS-MANAGER

Even on healthy and balanced grassland an annual maintenance is absolutely essential. The long-established grassland weeder GRASS-MANAGER is especially designed for that purpose. It aerates and dethatches the turf. Furthermore, it crushes plants residues, manures and mixes the material.

A GRASS-MANAGER with pneumatic seed drill results in the PNEUMATICSTAR.



Type/ working width cm	Sections	Feeler wheels	Tines	from HP/kW	Weight approx. kg / lbs
RIGID non folding:					
GRASS-MANAGER 150	1x1,5	2	60	20/15	190 kg 419 lbs
GRASS-MANAGER 200	1x2,1	2	84	25/18	200 kg 441 lbs
GRASS-MANAGER 300	2x1,5	2	120	30/22	250 kg 551 lbs
Hydraulic retraction:					
GRASS-MANAGER 450	3x1,5	4	180	40/29	520 kg 1146 lbs
GRASS-MANAGER 500	1x2,1 / 2x1,5	4	204	50/37	540 kg 1190 lbs
GRASS-MANAGER 600	4x1,5	4	240	60/44	640 kg 1410 lbs
GRASS-MANAGER 600 SR	4x1,5	4	240	60/44	800 kg 1764 lbs
GRASS-MANAGER 750	5x1,5	4	300	70/51	850 kg 1874 lbs
GRASS-MANAGER 900 ^{1,3)}	6x1,5	4	360	80/59	1170 kg 2579 lbs
GRASS-MANAGER 900 SR ³⁾	6x1,5	4	360	80/59	1260 kg 2778 lbs
GRASS-MANAGER 1200 ^{2,3)}	8x1,5	4	480	90/66	1310 kg 2888 lbs
GRASS-MANAGER 1200 SR ³⁾	8x1,5	4	480	90/66	1420 kg 3131 lbs

1) Can be extended to 12 m / 39.40 ft. working width

2) Can be reduced to 9 m / 29.50 ft. working width

3) Hydraulic folding with shear retraction

SR = heavy frame for contractors or communities

STANDARD EQUIPMENT

- ✓ Tines ø 8 mm / 0.31", 490 mm / 19.29" long | individually exchangeable | 10 cm wear length
- ✓ Real line spacing 2.5 cm / 1"
- ✓ Sturdy, durable plastic tine holder
- ✓ Tube frame section providing equal working pressure over the full section width
- ✓ 6 row tine section with central tine adjustment per section
- ✓ 5-stage adjustable angle of the tines
- ✓ Lower links with quick coupling pendular axle (up to article 55060)
- ✓ Sturdy tube frame | adjustable rubber support wheels | parking support for hydr. foldable machines
- ✓ Large bearing mounted rubber support wheels, dimension 16x6.50/80 (for machines with shear-folding 18x8.50-8)
- ✓ The side sections swing in automatically through parallel guidance (for hydr. foldable machines)

OPTIONS

- » Hydraulic tine adjustment (not in combination with front levelling plates)
- » Front levelling plates (up to 6 m / 20ft working width and all SR)
- » Tines 490 mm / 19.3 long, Ø 10 mm / 0.39" (only for SR models)
- » Tines 490 mm / 19.3 long STRAIGHT, Ø 8 mm / 0.31"
- » Hydraulic transport lock
- » Track width up to 2,15 m / 85"
- » Pneumatic seeder P-BOX
- » Warning signs with holder and LED-light



The universal machine for grassland, as well as mechanical weed control in field crops (cereals, corn, soybeans,...)