



Note:

1.Material:

1.1 Insulator: PBT UL 94-V0 rated.

1.2 Contact: Brass,t=0.25mm.

1.3 Shell: Cold rolled steel,t=0.30mm.

2.Specification:

2.1 Current rating: 1 A Max.

2.2 Dielectric withstanding voltage: 500 V(ac) for 1 minute.

2.3 Contact resistance: 30 mΩ Max.

2.4 Insulation resistance: 1000 mΩ Min at DC 500V.

2.5 Temperature range: -55°C~+105°C.

3.Finishes:

3.1 Contacts: Gold flashed 1u",3u",5u",10U",15u",30u".

3.2 Shell: Nickel plated.

4	FRONT SHELL	1	Cold rolled steel	T=0.30±0.02mm	Nickel Plated
3	BACK SHELL	1	Cold rolled steel	T=0.30±0.02mm	Nickel Plated
2	CONTACT	4	Brass	T=0.25±0.02mm	Gold Flashed
1	HOUSING	1	PBT		White/black
No.	Part Name	Q'ty	Material	Thickness	Finish

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Angel	SCALE 比例 参考	TOLERANCE UNSPECIFIED x ±0.30 xx ±0.20 xxx ±0.100 ANG. 41*
DWG. 製圖 Yumi	UNIT 單位 M M	SIZE. 紙張尺寸 A 4
DATE 制表日 2008/02/14	PAGE 張數 1 OF 1	REV. 版次 A
PART NAME 品名 USB (MALE) HOUSING 4P A TPYE WHITE LOW-LEAD		PART NO. 料號 C8319-04AMSXW0R