



MATERIAL

- 1. BODY: LCP UL 94V-0 RATED,COLOR:BLACK;
- 2. COVER: LCP UL94V-0 RATED,COLOR:BLACK;
- 3. CONTACT: PLATING:GOLD PLATING OVER NICKEL
ON CONTACT AREA,TIN/LEAD PLATING
ON TERMINAL.

SPECIFICATION

- 1. CURRENT RATING: 0.5 AMP. MAX.;
- 2. DIELECTRIC WITHSTANDING VOLTAGE:
500V AC R.M.S FOR ONE MINUTE;
- 3. INSULATION RESISTANCE:1000 M OHMS MIN.
AT 500V AC;
- 4. CONTACT RESISTANCE:30m OHMS MAX.
- 5. OPERATING TEMPERATURE: -25°C TO +85°C
- 6. PROCESSING TEMP:230°C FOR 30~60
SECONDS MAX.;
- 7. DURABILITY: 5000 CYCLES.

F			
E			
D			
C			
B			
A	07-02-2002	ICA-501-008(CF2)	Jun
REV	DATE	FILE	BY

DRAWN: Jerry Chen
CHECKED: Ruby
APPROVAL: Mike Wu

GENERAL TOLERANCE: .X=±0.2 .XX=±0.15
UNIT: MM
SCALE:
SHEET: 1 / 1
PROJECTION:



DESCRIPTION: SIM CARD 08 PINS	SIZE A4
PART NO: ICA-501-008	

A
B
C
D